

*Rely on us.*SM

dayGraphica® 48 Coaterstrip PB

Polyester backed coating blanket

Stripping blanket for coating and varnishing applications

Product Features

- dayGraphica® 48 Coaterstrip PB gives perfect register on repeat runs due to its non stretch properties.
- Deep stencil depth is provided by complete removal of blanket surface right down to the cut resistant polyester layer (except on 1.96mm gauge, which strips to the compressible layer) ensures long, uninterrupted production. Clean stencil edges can be achieved either by hand or CAD cutting.
- dayGraphica® 48 Coaterstrip PB's dual compatibility surface rubber is highly resistant to UV chemical attack, making the dayGraphica® 48 Coaterstrip PB the ideal blanket for long and repeat production runs with either aqueous or UV coatings.

Advantages of dayGraphica® 48 Coaterstrip PB

- Non stretch.
- Excellent smash recovery.
- Easy stencil peeling.
- Versatile, suitable for both aqueous and UV coating applications.

dayGraphica® 48 Coaterstrip PB

Features	Benefits
<ul style="list-style-type: none">• Cast/micro ground surface.	<ul style="list-style-type: none">• Even laydown of all coating finishes.• CAD friendly for trouble free stencil cutting.
<ul style="list-style-type: none">• Thick compressible/stripping layer.	<ul style="list-style-type: none">• Ensures excellent recovery from smashes.• Compensates for uneven stock.• Easy peeling.
<ul style="list-style-type: none">• Dual compatibility surface compound.	<ul style="list-style-type: none">• Optimum coating transfer with both aqueous and UV coatings.
<ul style="list-style-type: none">• Polyester base.	<ul style="list-style-type: none">• Perfect register on repeat runs.• High stability.• Cut resistant.

Colour	Turquoise
Face compound	Solvent resistant rubber blend
Microhardness	68°
Tensile strength	>60 N/mm
Peel strength	15 to 25 N/mm
Coating compatibility	Water based and UV

Surface finish	Thickness	Stencil depth
<ul style="list-style-type: none">• Cast	<ul style="list-style-type: none">• 1.96mm	<ul style="list-style-type: none">• 0.80mm
<ul style="list-style-type: none">• Micro Ground	<ul style="list-style-type: none">• 1.35mm	<ul style="list-style-type: none">• 1.00mm
<ul style="list-style-type: none">• Micro Ground	<ul style="list-style-type: none">• 1.30mm	<ul style="list-style-type: none">• 0.95mm
<ul style="list-style-type: none">• Micro Ground	<ul style="list-style-type: none">• 1.15mm	<ul style="list-style-type: none">• 0.80mm

More products. Streamlined access. Greater results.

Flint Group's Print Media division offers a uniquely powerful combination of products, services and expertise; giving you access to the industry's broadest range of pressroom products.

Inks and Coatings. Pressroom Chemicals. Blankets. Sleeves. Consumables.

Rely on us for consistency, reliability and customer focus. Our aim is to make it easier for you to achieve your business goals. With Flint Group products in your pressroom, you can run your business with confidence and peace of mind.

You are welcome to contact us for further information.

Print Media Europe
Balgray Street,
Dundee, DD3 8HN,
Scotland, UK.

T +44 (0)1382 422200
F +44 (0)1382 819051
printmedia.eu@flintgrp.com
www.flintgrp.com

The aim of our technical documents is to inform our customers about general values. However, the transferability of general values known from experience and laboratory results to concrete practical applications depends on a number of factors which are beyond our control. We therefore ask for your understanding that this advice document cannot be used as the basis for claims in law. Furthermore, the correct application for each product has to be checked carefully for suitability.

Product names followed by ® are trademarks registered by Flint Group Incorporated.