


Technical Data Sheet

SENOLITH® STANDARD OVERPRINT COATINGS











SENOLITH® WB FP SATIN MATT COATING

17-5341 40F 1010







SENOLITH® WB FP SATIN MATT COATING 40F 1010 is a satin matt, transparent, water-based polymer dispersion varnish.

Field of application	Varnishing of coated papers and cardboards	
Special features	Very high wet block resistance	
Varnishing on both sides	Suited	
Processing	Embossing	Suited
	Hot foil stamping	Suited with appropriate foils
	Gluability	Suited with appropriate glues

Product specifications

 pH	8,20	 Very fast drying	 35 s 4 mm 20°C
 Satin matt		 Very good abrasion resistance	 Storage temperature not above 30 °C
 Storage temperature not below 5 °C		 Shelf life: 12 months	

Application data

 wet- g/m ²	Application quantity approx. 3 – 4 g/m ²	 99V 9800 SENOLITH® CLEANING AGENT FOR WATER BASED SYSTEMS	 Stir thoroughly prior to use
 Hot-air blast, IR radiation, powder application when required		 Chambered doctor blade	 Coated papers and cardboards

General information

Stir varnish thoroughly before use!

Before production run we recommend preliminary tests!

Please also read our data sheet regarding the general processing of dispersion varnishes.